





3DA325 (2SD325) 型 NPN 硅高频大功率晶体管

参数符号		测试条件	规范值	单位
极 限 值	P _{CM}	T _C =25℃	1.75	W
	I _{CM}		1.5	A
	T _{jm}		150	℃
	T _{stg}		-55~150	℃
	R _{th}	V _{CE} =10V I _C =0.3A	71	℃/W
直 流 参 数	V _{(BR)CBO}	I _{CB} =1mA	≥35	V
	V _{(BR)CEO}	I _{CE} =1mA	≥35	V
	V _{(BR)EBO}	I _{EB} =1mA	≥5.0	V
	I _{CBO}	V _{CB} =20V	≤0.1	μA
	I _{EBO}	V _{CE} =5.0V	≤1.0	μA
	V _{BEsat}	I _C =1.5A	≤1.5	V
	V _{CEsat}	I _B =0.15A	≤1.0	
	h _{FE}	V _{CE} =2.0V I _C =1.0A	40~320	
		V _{CE} =2.0V I _C =0.1A	≥35	
交 流 参	f _T	V _{CE} =5V I _C =0.5A fo=1.0MHz	≥8.0	MHz
外 引 线 说 明	 SMD-1  B2-01B(F1)  TO-220  TO-257 1. E 发射极 2. B 基 极 3. C 集电极			
替代型号：2SD325				